



## FARM HIGHWAY TOUGH - Data Sheet

### Description

FARM HIGHWAY TOUGH is a high-speed tire designed for transport and soil tillage applications with trailers and implement machinery. It provides high load capacity also at high speeds and ensures a long tire life-cycle.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Implement Machinery • Trailer



SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.00 - 15 FI	STANDARD	94044733	128 J	8	8 LB		10.8	33.6	0	0	TL	E11-54R-0017870
11L - 15 FI	STANDARD	94032518	128 J	12	8 LB	10 LB ; 8 J	11	30.6	13.7	87.2	TL	E11-54R-0017871
11L - 15 FI	STANDARD	94039937	120 J	8	8 LB	10 LB ; 8 J	11	30.6	13.7	87.2	TL	E11-54R-0018902
12.5L - 15 FI	STANDARD	94032525	134 J	12	10 LB		12.5	32.1	14.3	91.5	TL	E11-54R-0019049
9.5L - 15 FI	STANDARD	94037605		12	7.00	8 LB	9.6	30.2	13.5	85.9	TL	
9.5L - 15 FI	STANDARD	94039920		8	7.00	8 LB	9.6	30.2	13.5	85.9	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/23/2025 2:21 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..