

## FARM SPECIAL - Technical Specifications



### Description

FARM SPECIAL is a tractor tire suitable for soil tillage operations. The strong casing provides a high level of puncture resistance and a longer service life, whilst the rounded shoulders prevent soil damages ensuring the protection of the valuable crops. FARM SPECIAL features a unique tread design with special mud breakers for best self-cleaning properties. In addition, dual angled lugs provide excellent traction and reduced slippage.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TT
Tyre Size	12.4 - 28
LI/SS	120 A8

Dimensions US Standard

Usa code	94060726
Ply Rating	8
Section Width (inch)	12.4
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	23.2
Rolling Circumference (inch)	151.7
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-005533
TRA Code	R1

Load capacity (lbs)

mph / psi	34
25	3090

Printed on 4/29/2024 1:44 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..