

FL 252 - Technical Specifications



Description

FL 252 is a tire suitable for hay harvesting applications with rotor rakes/tedders as well as for logistic operations using forklifts. This tire provides excellent durability while the specific tread pattern ensures maximum stability during lifting operations.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Rotor Rake / Tedder
Industrial: Forklift

Version	STANDARD
Type	TT
Tyre Size	8.15 - 15 (28 X 9 - 15)

Dimensions US Standard

Usa code	94006915
Ply Rating	14
Section Width (inch)	8.7
Overall Diameter (inch)	28.3
Rim Rec	7.00
Rim Alt	7 BD

Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	8600
15 STEER WHEEL	6615
5 OTHER VEHICLES	8600
15 OTHER VEHICLES	6615
STATIC SIDE LOADER	9985

Printed on 4/26/2024 7:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..