

FL 630 SUPER - Technical Specifications



Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	161 D

Dimensions US Standard

Usa code	94042166
Section Width (inch)	21.4
Overall Diameter (inch)	49
Static Loaded Radius (inch)	21.6
Rolling Circumference (inch)	149
Rim Rec	AG 16.00
Rim Alt	17.00 ; 20.00
ECE	E4-106R-000794

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	3000	3470	3940	4680	5530	6330	7030	7870	8620	9370
40	3260	3780	4290	5100	6020	6890	7650	8560	9380	10200
30	3960	4570	5190	6170	7290	8330	9260	10370	11360	12350
25	4440	5140	5830	6930	8190	9370	10410	11650	12760	13870
15	5160	5970	6780	8060	9510	10880	12090	13550	14840	16110
5	5870	6800	7720	9180	10840	12390	13770	15420	16890	18350

Printed on 4/23/2024 3:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..