



FL 630 SUPER - Data Sheet

Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer



SIZE	Version	USACode	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
560/60 R 22.5	STANDARD	94042166	161 D			AG 16.00	17.00 ; 20.00	21.4	49	21.6	149	TL	E4-106R-000794
560/60 R 22.5	STANDARD	94059539	165 D			AG 16.00	17.00 ; 20.00	21.4	49	21.6	149	TL	E11-106R-006945
580/65 R 22.5	STANDARD	94045037	166 D			AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	22.7	52.2	23.4	159.8	TL	E4-106R-001416
580/65 R 22.5	STANDARD	94073221	174 D	174 D	174 D	AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	22.9	52.2	23.4	159.8	TL	E11-106R-008289
600/50 R 22.5	STANDARD	94060900	159 D			AG 20.00		24.1	46.1	20.4	139.1	TL	E11-106R-005992
600/55 R 22.5	STANDARD	94056149	162 D			AG 20.00		23.4	48.5	22	147.9	TL	E11-106R-004759
600/55 R 26.5	HD	94048946	177 D			AG 20.00		24.1	52.5	23.8	161.6	TL	E11-106R-003005
600/55 R 26.5	STANDARD	94040476	165 D			AG 20.00		24.1	52.5	23.9	160.6	TL	E4-106R-001414
650/55 R 26.5	HD	94048953	178 D			AG 20.00		25.4	54.7	24.7	169	TL	E11-106R-003006
650/55 R 26.5	STANDARD	94038855	169 D			AG 20.00		25.4	54.7	24.7	167.6	TL	E4-106R-000806
650/65 R 26.5	STANDARD	94045587	174 D			AG 20.00		25.4	59.8	26.9	183.2	TL	E4-106R-001651
710/50 R 26.5	STANDARD	94053445	170 D			AG 24.00	AG 20.00	28.6	54.4	24.6	166.8	TL	E11-106R-003009
750/45 R 26.5	STANDARD	94046096	170 D			AG 24.00		29.7	53.1	23.9	163.3	TL	E4-106R-001652
750/60 R 26.5	STANDARD	94042135	180 D			AG 24.00		29.7	62	27.3	189	TL	E4-106R-001427
650/65 R 30.5	STANDARD	94045594	176 D			AG 20.00		25.4	63.8	28.9	195.9	TL	E4-106R-001653
750/60 R 30.5	STANDARD	94041190	181 D			AG 24.00		29.7	65.9	29.4	201.4	TL	E4-106R-001499
850/50 R 30.5	STANDARD	94073191	182 D	182 D	182 D	AG 28.00		33.9	64	28.4	192.7	TL	E11-106R-008232

Printed on 4/23/2024 12:06 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..