

## FL 635 - Data Sheet



### Description

FL 635 is a radial flotation tire suitable for both road and field usage. The special block pattern has been designed for hay baler applications. FL 635 ensures a great pressure distribution on the ground across the footprint and drastically reduces soil compaction to preserve the value of the crops. The tire ensures great self-cleaning properties, durability and traction along with excellent speed features.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Baler

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
500/45 R 22.5	STANDARD	136 D	AG 16.00		490	1022	461	3086	500	TL	E11-106R-0010082
620/40 R 22.5	STANDARD	154 D	AG 20.00		625	1068	470	3249	500	TL	E4-106R-002399
650/55 R 22.5	STANDARD	167 D	AG 20.00		645	1287	568	3901	600	TL	E4-106R-000803
710/40 R 22.5	STANDARD	161 D	AG 24.00		727	1140	510	3467	550	TL	E11-106R-003014
750/45 R 22.5	STANDARD	168 D	AG 24.00		754	1247	555	3810	600	TL	E4-106R-002653

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 1:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..