

FLOTATION 351 - Data Sheet

Description

FLOTATION 351 is a bias flotation tire which best suits transport applications using trailers. Extra deep lugs provide outstanding traction and a longer tire life. FLOTATION 351 is the ideal tire on wet and moist surfaces ensuring high load capacity.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Trailer



SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
42 X 25.00 - 20	STANDARD	HF3	135 B	12	20.50 HF	20.50 VF	605	1110	508	3302	TL	E11-106R-004382
42 X 25.00 - 20	STANDARD	HF3	139 B	16	20.50 HF	20.50 VF	605	1110	508	3302	TL	E11-106R-004383
48 X 25.00 - 20	STANDARD	HF3	144 B	10	20.50 HF	20.50 VF	630	1270	559	3785	TL	
48 X 31.00 - 20	STANDARD	HF3	148 B	12	26.00 HF	26.00 VF	775	1283	559	3886	TL	E11-106R-004385
66 X 43.00 - 25	STANDARD	HF3	170 B	16	36.0 TH		1020	1750	782	5213	TL	E11-106R-003346
66 X 43.00 - 25	STANDARD	HF3	150 B	6	36.0 TH		1020	1750	782	5213	TL	
66 X 43.00 - 25	STANDARD	HF3	160 B	10	36.0 TH		1020	1750	782	5213	TL	E11-106R-004378

Printed on 4/23/2024 11:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..