

FLOTATION 558 - Data Sheet



Description

FLOTATION 558 is a cross-ply flotation tire suitable for hay harvesters/balers, tankers and trailers both on and off the road. It is particularly recommended whenever traction is essential for good soil tillage in addition to high load capacity.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Hay Harvester • Tanker • Trailer

| SIZE | Version | USACode | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|---------------|------------------|----------|-------------------|--------------------|----|----------|--------------------------|------|------|------|-------|------|-----------------|
| 400/55 - 22.5 | ARAMID BELTED HD | 94048298 | 140 A8/136 B | 152 A8/148 B | 16 | AG 11.75 | 12.25 ; 13.00 ; AG 13.00 | 15.9 | 40.2 | 17.5 | 121.4 | TL | E11-106R-005350 |
| 400/55 - 22.5 | STANDARD | 94058501 | 144 A8/140 B | 156 A8/152 B | 20 | AG 11.75 | 12.25 ; 13.00 ; AG 13.00 | 15.9 | 40.2 | 17.5 | 121.4 | TL | E11-106R-005351 |
| 400/55 - 22.5 | STANDARD | 94006243 | 138 A8/134 B | 150 A8/146 B | 14 | AG 11.75 | 12.25 ; 13.00 ; AG 13.00 | 15.9 | 40.2 | 17.5 | 121.4 | TL | E4-106R-002261 |
| 400/55 - 22.5 | STANDARD | 94006250 | 140 A8/136 B | 152 A8/148 B | 16 | AG 11.75 | 12.25 ; 13.00 ; AG 13.00 | 15.9 | 40.2 | 17.5 | 121.4 | TL | E4-106R-002262 |
| 500/45 - 22.5 | ARAMID BELTED HD | 94048281 | 142 A8/138 B | 154 A8/150 B | 16 | AG 16.00 | | 19.7 | 41.1 | 18.5 | 124.7 | TL | E11-106R-005352 |
| 500/45 - 22.5 | STANDARD | 94006267 | 136 A8/132 B | 148 A8/144 B | 12 | AG 16.00 | | 19.7 | 41.1 | 18.5 | 124.7 | TL | E4-106R-002307 |
| 500/45 - 22.5 | STANDARD | 94006274 | 142 A8/138 B | 154 A8/150 B | 16 | AG 16.00 | | 19.7 | 41.1 | 18.5 | 124.7 | TL | E4-106R-002315 |
| 500/45 - 22.5 | STANDARD | 94058518 | 146 A8/142 B | 158 A8/154 B | 20 | AG 16.00 | | 19.7 | 41.1 | 18.5 | 124.7 | TL | E11-106R-005353 |

Printed on 12/8/2023 7:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..