

FLOTATION 648 T - Technical Specifications

Description

FLOTATION 648 T is particularly suitable for hay harvesting as well as for field and road transport. The special tread design allows for carrying very heavy loads at low pressure and ensures outstanding self-cleaning properties. The tire also stands for excellent traction and durability.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Hay Harvester



Version	STANDARD
Type	TL
Tyre Size	550/45 - 22.5
LI/SS DRIVE WHEEL	147 A8/144 B
LI/SS FREE ROLLING	159 A8/156 B

Dimensions International Standard

Ply Rating	16
Section Width (mm)	550
Overall Diameter (mm)	1070
Static Loaded Radius (mm)	475
Rolling Circumference (mm)	3203
Rim Rec	AG 16.00

Load capacity (Kg)

km/h / bar	2.40	2.60	2.80
10 FR	5600	5865	6125
20 FR	5040	5280	5515
30 FR	4480	4695	4900
40 FR	4000	4190	4375
50 FR	3600	3770	4000
10 DW	3935	4125	4305
20 DW	3540	3710	3875
30 DW	3145	3300	3445
40 DW	2810	2945	3075
50 DW	2530	2650	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/4/2024 1:54 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..