

FLOTATION RIB 774 - Technical Specifications



Description

FLOTATION RIB 774 is suitable in all free-rolling applications, hay harvesting applications and ideal for trailers. It has been designed to provide best handling comfort optimizing the timing of operations as well as high load capacity and a longer tire life.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Harvester • Hay Harvester • Trailer

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 550/60 - 22.5 |
| LI/SS FREE ROLLING | 160 A8/156 B |

Dimensions International Standard

| | |
|-----------------------------------|-----------------|
| Ply Rating | 12 |
| Section Width (mm) | 550 |
| Overall Diameter (mm) | 1240 |
| Static Loaded Radius (mm) | 540 |
| Rolling Circumference (mm) | 3725 |
| Rim Rec | AG 16.00 |
| ECE | E11-106R-005941 |

Load capacity (Kg)

| km/h / bar | 1.50 | 1.80 | 2.10 |
|-------------------|-------------|-------------|-------------|
| 10 FR | 5175 | 5755 | 6300 |
| 20 FR | 4655 | 5180 | 5670 |
| 30 FR | 4140 | 4605 | 5040 |
| 40 FR | 3695 | 4110 | 4500 |
| 50 FR | 3325 | 3700 | 4000 |

Printed on 4/24/2024 4:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..