FLOTATION RIB 774 - Technical Specifications

Description

FLOTATION RIB 774 is suitable in all free-rolling applications, hay harvesting applications and ideal for trailers. It has been designed to provide best handling comfort optimizing the timing of operations as well as high load capacity and a longer tire life.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Harvester • Hay Harvester • Trailer

Version	STANDARD
Type	TL
Tyre Size	600/55 - 22.5
LI/SS FREE ROLLING	164 A8/160 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	600
Overall Diameter (mm)	1230
Static Loaded Radius (mm)	540
Rolling Circumference (mm)	3716
Rim Rec	AG 20.00
ECE	E11-106R-005943

Load capacity (Kg)

km/h / bar	1.50	1.70	2.00
10 FR	5915	6365	7000
20 FR	5325	5725	6300
30 FR	4730	5090	5600
40 FR	4225	4545	5000
50 FR	3805	4090	4500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 10:51 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..