

FLOTATION TR 675 - Technical Specifications



Description

FLOTATION TR 675 is best suited for field and road transport. It fits trailers and implement machinery. FLOTATION TR 675 has been engineered to provide outstanding traction, high load capacity and a longer tire life.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Trailer

| | |
|--------------------|---------------|
| Version | DUAL BEAD |
| Type | TL |
| Tyre Size | 500/60 - 22.5 |
| LI/SS DRIVE WHEEL | 155 A8/151 B |
| LI/SS FREE ROLLING | 168 A8/164 B |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94050147 |
| Ply Rating | 20 |
| Section Width (inch) | 20.3 |
| Overall Diameter (inch) | 46.5 |
| Static Loaded Radius (inch) | 21.3 |
| Rolling Circumference (inch) | 141.9 |
| Rim Rec | AG 16.00 |
| Rim Alt | 15.00 ; 17.00 |
| ECE | E11-106R-004395 |

Load capacity (lbs)

| mph / psi | 54 | 55 | 58 |
|-----------|-------|-------|-------|
| 5 FR | 16370 | 16630 | 17280 |
| 10 FR | 14740 | 14970 | 15550 |
| 20 FR | 13090 | 13300 | 13820 |
| 25 FR | 11690 | 11880 | 12350 |
| 30 FR | 10530 | 10690 | 11020 |
| 5 DW | 11580 | 11770 | 11960 |
| 10 DW | 10430 | 10590 | 10770 |
| 20 DW | 9270 | 9420 | 9570 |
| 25 DW | 8280 | 8410 | 8540 |
| 30 DW | 7450 | 7570 | 7610 |

Printed on 5/3/2024 3:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..