

FLOTATION TR 678 - Technical Specifications



Description

FLOTATION TR 678 has been specially designed for trailers and agricultural implements both on- and off the road. This tire allows for carrying very heavy loads at low pressure ensuring reduced soil compaction at the same time. It provides excellent traction and outstanding self-cleaning properties.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Trailer

| | |
|--------------------|---------------|
| Version | DUAL BEAD |
| Type | TL |
| Tyre Size | 600/40 - 22.5 |
| LI/SS DRIVE WHEEL | 157 A8 |
| LI/SS FREE ROLLING | 169 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94051915 |
| Ply Rating | 20 |
| Section Width (inch) | 24.2 |
| Overall Diameter (inch) | 42.7 |
| Static Loaded Radius (inch) | 19 |
| Rolling Circumference (inch) | 128.5 |
| Rim Rec | AG 20.00 |
| ECE | E11-106R-006501 |

Load capacity (lbs)

| | |
|-----------|-------|
| mph / psi | 60 |
| 25 | 12790 |

Printed on 2/26/2024 10:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..