

FLOTATION V LINE - Technical Specifications



Description

FLOTATION V LINE has been specially designed for trailers in transport applications. It shows high flotation capability and ensures low soil compaction protecting the field. FLOTATION V LINE allows you to carry high loads at low pressure maximizing your business productivity.

UM

International Standard

Construction

✚ BIAS

Machinery

Agriculture: Trailer

Version	STANDARD
Type	TL
Tyre Size	550/60 - 22.5
LI/SS DRIVE WHEEL	154 A8/150 B
LI/SS FREE ROLLING	167 A8/163 B

Dimensions International Standard

Ply Rating	16
Section Width (mm)	550
Overall Diameter (mm)	1240
Static Loaded Radius (mm)	540
Rolling Circumference (mm)	3725
Rim Rec	AG 16.00
ECE	E4-106R-001563

Load capacity (Kg)

km/h / bar	2.40	2.60	2.80
10 FR	6970	7310	7630
20 FR	6275	6575	6865
30 FR	5580	5845	6105
40 FR	4980	5220	5450
50 FR	4480	4700	4875
10 DW	4795	5025	5250
20 DW	4315	4525	4725
30 DW	3835	4020	4200
40 DW	3425	3590	3750
50 DW	3085	3230	3350

Printed on 4/29/2024 1:50 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..