

# GIANT TRAX - Technical Specifications



## Description

GIANT TRAX has been designed for skid steer loaders in scrap yard operations, on rough concrete surfaces, recycling applications and mines. The extra deep tread with wider and sturdier blocks provides best traction, stability, and puncture resistance. The special tread compound results in exceptional cut and chip resistance along with excellent wear resistance on all types of terrains.

## UM

US Standard

## Construction

 BIAS

## Machinery

Industrial: Skid Steer

Version	STANDARD
Type	TL
Tyre Size	14 - 17.5

Dimensions US Standard

Usa code	94064403
Ply Rating	14
Section Width (inch)	13.8
Overall Diameter (inch)	36
Static Loaded Radius (inch)	16.6
Rolling Circumference (inch)	106.9
Rim Rec	10.50
ECE	E11-106R-006019

Load capacity (lbs)

mph / psi	80
5	8540
10	6750
15	6240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 5:25 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..