

GR 288 - Technical Specifications



Description

GR 288 (G-2/L-2) is a versatile bias-ply tire for graders or loaders. It is ideal for use in construction, site preparation, road building, and other soft or muddy environments. The self-cleaning tread pattern provides excellent traction, and you can expect a long tire life as a result of the special cut-and-chip-resistant compound.

UM

International Standard

Construction

BIAS

Machinery

Industrial: Dozer • Loader

OTR: Grader

Version	DUAL BEAD HD
Type	TT
Tyre Size	17.5 - 25

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	445
Overall Diameter (mm)	1330
Static Loaded Radius (mm)	596
Rolling Circumference (mm)	3950
Rim Rec	14.00/1.5
Rim Alt	14.00/1.3 (DC)
ECE	E11-106R-005407
TRA Code	G2/L2

Load capacity (Kg)

km/h / bar	3.25	5.75
40	3650	-
10	-	8250

Printed on 5/4/2024 3:33 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..