

GRIP STAR - Data Sheet



Description

GRIP STAR is an agro-industrial tire for loading applications with telehandlers. It shows excellent traction and self-cleaning properties. Besides, it is an all-season tire particularly suitable for operations on muddy ground. GRIP STAR is also available in a "special" version that features extra cut and chip resistance.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Telehandler

SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type
15.5/80 - 24	SPECIAL	151 A6	163 A6	16	W 12	W 13 ; W 14 L	392	1270	569	3683	600	TL
15.5/80 - 24	STANDARD	151 A6	163 A6	16	W 12	W 13 ; W 14 L	392	1270	569	3683	600	TL
15.5/80 - 24	STANDARD	151 A6	163 A6	16	W 12	W 13 ; W 14 L	392	1270	569	3683	600	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 12:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..