

## IT 400 - Technical Specifications



### Description

IT 400 is a road-oriented rib-pattern tire for low platforms in transport applications. The tire is suitable for high-speed applications and provides significant fuel savings.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Low Platform Trailer

Version	STANDARD
Type	TT
Tyre Size	10.00 - 15
LI/SS	143/138 J

# Dimensions International Standard

Ply Rating	18
Section Width (mm)	274
Overall Diameter (mm)	925
Static Loaded Radius (mm)	408
Rolling Circumference (mm)	2747
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
ECE	E11-54R-0019537

## Load capacity (Kg)

km/h / bar	9.70	8.90	8.10
15	4510	-	-
30	-	3640	-
100 LS	-	2725	-
100 LD	-	-	2360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 4:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..