

IT 400 - Technical Specifications



Description

IT 400 is a road-oriented rib-pattern tire for low platforms in transport applications. The tire is suitable for high-speed applications and provides significant fuel savings.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Low Platform Trailer

Version	STANDARD
Type	TL
Tyre Size	8.25 - 15
LI/SS	129/125 J

Dimensions International Standard

Ply Rating	14
Section Width (mm)	239
Overall Diameter (mm)	846
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2513
Rim Rec	6.50
Rim Alt	6.0 ; 7.0
ECE	E11-54R-0018586

Load capacity (Kg)

km/h / bar	8.60	7.90	7.20
15	2960	-	-
30	-	2440	-
100 LS	-	1850	-
100 LD	-	-	1650

Printed on 4/23/2024 2:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..