

## LG 306 - Technical Specifications



### Description

LG 306 is a lawn and garden tire suitable for mowers. In some sizes, LG 306 is also fit for small tractors. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time. LG 306 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Mower • Small Tractor

Version	STANDARD
Type	TL
Tyre Size	26 X 12.00 - 12

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	310
Overall Diameter (mm)	640
Static Loaded Radius (mm)	283
Rolling Circumference (mm)	1856
Rim Rec	10.50 I - 55 ; I - 70 ; I - 90
Rim Alt	10½ JA ; 8½ JA
ECE	E11-106R-003524

## Load capacity (Kg)

km/h / bar	4.50
15	1600

Printed on 5/2/2024 11:54 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..