

## LG SMOOTH - Technical Specifications



### Description

LG SMOOTH is a lawn and garden tire suitable for mowers. While the tire is gentle on the ground, the enhanced design ensures increased durability and eases handling. LG SMOOTH is available in an "aramid-belted" version for users who need strengthened puncture resistance.

### UM

International Standard

### Construction

✚ BIAS

### Machinery

Agriculture: Mower • Small Tractor

Version	STANDARD
Type	TL
Tyre Size	18 X 10.50 - 10

## Dimensions International Standard

Ply Rating	2
Section Width (mm)	254
Overall Diameter (mm)	460
Static Loaded Radius (mm)	207
Rolling Circumference (mm)	1334
Rim Rec	8.5 I - 55 ; I - 70 ; I - 90
Rim Alt	8½ JA
ECE	E11-106R-005203

## Load capacity (Kg)

km/h / bar	0.80
15	334

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 8:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..