



LIFT STAR PLUS - Data Sheet



Description

LIFT STAR is a bias-ply tire specially designed for telehandlers operating in demanding construction operations and other severe applications. Its low-profile sidewall ensures excellent stability in high-lifting operations whereas its non-directional tread design allows for greater mounting versatility. In addition, the specially designed sidewall provides added cut-and-puncture protection.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Telehandler

| SIZE | Version | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|-------------|----------|----|----------|---------|-----|------|-----|------|------|-----------------|
| 370/75 - 28 | STANDARD | 14 | 11.00 | | 365 | 1270 | 583 | 3851 | TL | E11-106R-005331 |
| 400/75 - 28 | STANDARD | 16 | 12.00 GR | | 400 | 1318 | 592 | 3944 | TL | E11-106R-005330 |

Printed on 4/20/2024 4:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..