

LIFTMAX LM 81 - Technical Specifications



Description

LIFTMAX LM 81 has been specifically designed and engineered for heavy forklift and terminal tractors. Its aggressive and robust tread pattern together with the unique Antistatic tread compound ensure excellent wear properties and a long service life.

The strong All Steel casing and the reinforced sidewall provide maximum stability and handling during lift mode, together with a superior traction. In addition, its radial casing absorbs surfaces irregularities to provide a better riding comfort and increase operator confidence.

LIFTMAX LM 81 is Antistatic compliant, and all its sizes are capable of dissipating static charge from the vehicle.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Hay Harvester

Industrial: Forklift

Version	STANDARD
Type	TL
Tyre Size	16.00 R 25
LI/SS	200 A5

Dimensions US Standard

Usa code	94069071
Overall Width (inch)	17.3
Overall Diameter (inch)	60.2
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0

Load capacity (lbs)

mph / psi	145
15	30900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/13/2024 7:21 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..