MINE STAR - Data Sheet

Description

MINE STAR is a bias-ply tire which is an excellent choice for heavy-duty underground mining operations. It features high cut/chip and puncture resistance providing improved operational efficiency. MINE STAR is made of a special compound and features a special tread design resulting in an extended tire life-cycle.

UM

US Standard

Construction

BIAS

Machinery

OTR: Underground Mining Vehicle

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
32 X 14.50/15 - 15	STANDARD	94055135		28	11.0	11.50 ; 11.00 BD ; 10.50	13.8	32.5	0	0	TT
35 X 15 - 15	STANDARD	94045914		32	11.0	11.50 ; 11.00 BD	14.6	34.8	0	0	TT
35 X 15 - 15	STANDARD	94063253		20	11.0	11.50 ; 11.00 BD	14.6	34.8	0	0	TT
35 X 15 - 15	STANDARD	94069996		32	11.0	11.50 ; 11.00 BD	14.6	34.8	0	0	TL
38 X 16 - 15	STANDARD	94054886		32	11.5		15.7	39	0	0	TT
38 X 16 - 15	STANDARD	94070008		32	11.5		15.7	39	0	0	TL
8.25 - 15	STANDARD	94006946		20	6.5	6.0 ; 7.0	9.6	33.4	0	0	TT
55 X 19.00 - 25	STANDARD	94067879	L5	50	14.00		18.9	55.1	24.9	168.5	TL
55 X 19.00 - 34	STANDARD	94069897	L5	50	16.00		18.1	56.5	0	0	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 4:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..