

MULTIMAX MP 513 - Technical Specifications



Description

MULTIMAX MP 513 has been designed by BKT for multi-purpose vehicles in municipality/maintenance and transport applications, for both agricultural and industrial uses. It is perfect for universal vehicles and fertilizer trucks. Thanks to the strong steel-belted nylon casing, MULTIMAX MP 513 allows to carry heavy loads at high speeds providing a comfortable driving experience. It ensures a longer service life and traction along with outstanding self-cleaning properties.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Universal Vehicle • Fertilizer Truck
Industrial: Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	365/70 R 18 MPT
LI/SS	133 G

Dimensions US Standard

Usa code	94051366
Section Width (inch)	14.2
Overall Diameter (inch)	38.1
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	116.3
Rim Rec	11
Rim Alt	11 SDC ; 12 ; 12 SDC
ECE	E11-54R-0016138

Load capacity (lbs)

mph / psi	23	29	36	44	51	54
55	2380	2820	3350	3880	4410	4540
40	2580	3040	3640	4210	4780	4940
25	2760	3240	3860	4450	5070	5220

Printed on 4/23/2024 6:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..