

MULTIMAX MP 519 - Technical Specifications



Description

MULTIMAX MP 519 is a particularly suitable tire for light trucks in all transport applications. The steel-belted casing provides excellent stability at high-speed (90 km/h - 60 mph). Thanks to its low rolling resistance, the tire ensures reduced fuel consumption.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Light Truck

Version	STANDARD
Type	TL
Tyre Size	7.50 R 16 LT
LI/SS	112/110G

Dimensions International Standard

Ply Rating	8
Section Width (mm)	220
Overall Diameter (mm)	810
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2449
Rim Rec	6.00
Rim Alt	5.50 F ; 6 L ; 7 L
ECE	E11-54R-0019046

Load capacity (Kg)

km/h / bar	3.5
90 LS	1120
90 LD	1060

Printed on 4/28/2024 2:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..