

MULTIMAX MP 527 - Technical Specifications



Description

MULTIMAX MP 527 is a multi-purpose radial tire designed for telehandlers and compact loaders in agro-industrial applications. The tire shows a block pattern design providing excellent traction even on the harder surfaces. The strong sidewall ensures outstanding stability in lift mode. MULTIMAX MP 527 is made of a special cut-and-chip-resistant compound providing a long service life.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	340/80 R 20 IND
LI/SS	144 A8/B

Dimensions International Standard

Section Width (mm)	343
Overall Diameter (mm)	1052
Static Loaded Radius (mm)	483
Rolling Circumference (mm)	3176
SRI (mm)	500
Rim Rec	11
Rim Alt	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC
ECE	E11-106R-003957

Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1345	1600	1820	2075	2325	2495	2800	-	-
40	1345	1600	1820	2075	2325	2495	2800	-	-
30	1440	1710	1950	2220	2490	2670	3000	-	-
25	1495	1775	2025	2305	2585	2770	3110	-	-
10 Cyc.	1640	2020	2375	2730	3110	3385	3825	4035	4200
Static	2515	3095	3640	4190	4770	5185	5865	6185	6440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 4:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..