

## MULTIMAX MP 538 - Technical Specifications



### Description

MULTIMAX MP 538 is a radial multipurpose tire specifically designed for several applications and machineries: graders and loaders operating in winter conditions, as well as telehandlers, universal vehicles and sweepers in road maintenance.

Thanks to the strong steel-belted casing, MULTIMAX MP 538 allows to carry heavy loads even at high speeds. In addition, its unique tread design helps maintaining excellent traction on ice and snow.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Telehandler • Universal Vehicle  
Industrial: Grader • Loader

Version	STEEL BELTED
Type	TL
Tyre Size	405/70 R 20 MPT
LI/SS	152 G

## Dimensions International Standard

Section Width (mm)	407
Overall Diameter (mm)	1076
Static Loaded Radius (mm)	484
Rolling Circumference (mm)	3289
Rim Rec	W13

## Load capacity (Kg)

km/h / bar	6
90	3550
65	3850
40	4080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/5/2024 8:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..