

## PL 801 - Technical Specifications



### Description

PL 801 has been specially designed for hay harvesting applications with rotor rakes/tedders and for logistics operations with forklifts. It features excellent stability as well as high cut and chip resistance. PL 801 ensures an extended tire life-cycle.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Hay Harvester • Rotor Rake / Tedder • Forklift  
Industrial: Forklift

Version	STANDARD
Type	TT
Tyre Size	18 X 7 - 8 (180/70 - 8)
LI/SS	121 A8

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	173
Overall Diameter (mm)	470
Rim Rec	4.33 R
Rim Alt	5.00 F
ECE	E11-106R-003642

## Load capacity (Kg)

	km/h / bar	10.00
25 LOAD WHEEL		2145
25 STEER WHEEL		1650
10 OTHER VEHICLES		2145
25 OTHER VEHICLES		1650
STATIC SIDE LOADER		2490

Printed on 4/24/2024 6:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..