

PORTMAX PT 93 - Technical Specifications



Description

PORTMAX PT 93 is a terminal tractor and trailer tire, which has been specifically engineered for heavy-duty operations in terminal environments such as ports and logistic hubs. The special antistatic tread compound ensures excellent wear and heat resistance even under the most demanding operating conditions. PORTMAX PT 93 offers excellent handling features and outstanding grip along with enhanced durability.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Terminal Tractor • Trailer

Version	INDUSTRIAL
Type	TL
Tyre Size	310/80 R 22.5
LI/SS	175 A8

Dimensions US Standard

Usa code	94057764
Overall Width (inch)	12.1
Overall Diameter (inch)	42.1
Rim Rec	9.00

Load capacity (lbs)

mph / psi	145
25	15200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 3:05 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..