

PORTMAX PT 93 - Data Sheet



Description

PORTMAX PT 93 is a terminal tractor and trailer tire, which has been specifically engineered for heavy-duty operations in terminal environments such as ports and logistic hubs. The special antistatic tread compound ensures excellent wear and heat resistance even under the most demanding operating conditions. PORTMAX PT 93 offers excellent handling features and outstanding grip along with enhanced durability.

UM

International Standard

Construction



RADIAL

Machinery

Industrial: Terminal Tractor • Trailer

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	Type
280/75 R 22.5	INDUSTRIAL	168 A8	8.25	9.00	282	998	TL
310/80 R 22.5	INDUSTRIAL	175 A8	9.00		308	1070	TL
315/60 R 22.5	INDUSTRIAL	170 A8	9.75	9.00	307	965	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 11:25 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..