



RIB 324 - Data Sheet

Description

RIB 324 has been designed with a special block tread pattern and a large contact area to provide best stability and flotation features on loose soil and sandy terrain. The strong nylon casing and sidewall along with a special tread compound stand for excellent resistance against punctures and wear as well as higher load capacity.



UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery

Industrial: Trailer

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type
66 X 44.00 - 25	STANDARD	94064274	20	36.0 TH		43.7	66.9	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 10:43 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..