

RIB 713 - Technical Specifications



Description

RIB 713 is a steel-belted tire for agricultural implements. As a response to the increasing awareness of low soil compaction in modern farming, RIB 713 has been designed with IF technology. This enables the tire to carry heavier loads at lower inflation pressures and provides a larger footprint with uniform weight distribution. The steel-belted structure provides excellent puncture resistance and hence increased protection against stub penetration and relative damage, even if running into strong stubble. In addition, "D" speed rating (65 km/h - 40 mph) allows for fast road transfers. RIB 713 is BKT's contribution to maximize both the productivity and efficiency of your farming business

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Implement Machinery

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	IF 240/80 R 15
LI/SS	129 D

Dimensions US Standard

Usa code	94047925
Section Width (inch)	9.4
Overall Diameter (inch)	30.1
Static Loaded Radius (inch)	13.9
Rolling Circumference (inch)	91.5
Rim Rec	W 8
ECE	E11-106R-002971
TRA Code	I1

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	73
From 5 to 40 mph	1190	1510	1840	2080	2410	2730	3020	3310	3640	4080

Printed on 4/30/2024 7:35 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..