



## RIB 713 - Data Sheet



### Description

RIB 713 is a steel-belted tire for agricultural implements. As a response to the increasing awareness of low soil compaction in modern farming, RIB 713 has been designed with IF technology. This enables the tire to carry heavier loads at lower inflation pressures and provides a larger footprint with uniform weight distribution. The steel-belted structure provides excellent puncture resistance and hence increased protection against stub penetration and relative damage, even if running into strong stubble. In addition, "D" speed rating (65 km/h - 40 mph) allows for fast road transfers. RIB 713 is BKT's contribution to maximize both the productivity and efficiency of your farming business

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Implement Machinery

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	TKPH	ECE
IF 240/80 R 15	STUBBLE RESISTANT	I1	129 D	W 8		240	765	354	2324	360	TL		E11-106R-002971
IF 265/85 R 15 (10.5L R15)	STUBBLE RESISTANT	I1	121 D	W 8		260	831	368	2502	390	TL		E11-106R-003956
IF 280/70 R 15	STUBBLE RESISTANT	I1	134 D	W 8		279	779	347	2356	360	TL	1	E11-106R-005094
IF 280/70 R 15	STUBBLE RESISTANT	I1	128 D	W 8		279	779	347	2356	360	TL		E4-106R-001820
IF 320/70 R 15	STUBBLE RESISTANT	I1	146 D	W10		320	823	367	2590	390	TL		E11-106R-003959

Printed on 4/17/2024 4:23 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..