



RIB 713 - Data Sheet



Description

RIB 713 is a steel-belted tire for agricultural implements. As a response to the increasing awareness of low soil compaction in modern farming, RIB 713 has been designed with IF technology. This enables the tire to carry heavier loads at lower inflation pressures and provides a larger footprint with uniform weight distribution. The steel-belted structure provides excellent puncture resistance and hence increased protection against stub penetration and relative damage, even if running into strong stubble. In addition, "D" speed rating (65 km/h - 40 mph) allows for fast road transfers. RIB 713 is BKT's contribution to maximize both the productivity and efficiency of your farming business

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Implement Machinery

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH	ECE
IF 240/80 R 15	STUBBLE RESISTANT	94047925	I1	129 D	W 8		9.4	30.1	13.9	91.5	TL	0	E11-106R-002971
IF 265/85 R 15 (10.5L R15)	STUBBLE RESISTANT	94053612	I1	121 D	W 8		10.2	32.7	14.5	98.5	TL	0	E11-106R-003956
IF 280/70 R 15	STUBBLE RESISTANT	94052721	I1	134 D	W 8		11	30.7	13.7	92.8	TL	1	E11-106R-005094
IF 280/70 R 15	STUBBLE RESISTANT	94046201	I1	128 D	W 8		11	30.7	13.7	92.8	TL	0	E4-106R-001820
IF 320/70 R 15	STUBBLE RESISTANT	94050710	I1	146 D	W10		12.6	32.4	14.4	102	TL	0	E11-106R-003959

Printed on 4/17/2024 8:20 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..