

## RIB 774 (A) - Technical Specifications



### Description

RIB 774 (A) is a low-section implement tire offering high load capacity and a long tire life-cycle. It is suitable for hay harvesting and transport applications with balers and trailers.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Baler • Hay Harvester • Trailer

Version	STANDARD
Type	TL
Tyre Size	250/65 - 14.5
LI/SS FREE ROLLING	124 A8

## Dimensions International Standard

<b>Ply Rating</b>	14
<b>Section Width (mm)</b>	255
<b>Overall Diameter (mm)</b>	690
<b>Static Loaded Radius (mm)</b>	303
<b>Rolling Circumference (mm)</b>	1978
<b>Rim Rec</b>	AG 8.00
<b>Rim Alt</b>	6.75
<b>ECE</b>	E11-106R-003374

## Load capacity (Kg)

	km/h / bar	5.50
	10 FR	2240
	25 FR	1905
	30 FR	1790
	40 FR	1600

Printed on 4/23/2024 10:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..