

## RIB 774 (C) - Technical Specifications



### Description

RIB 774 (C) is a low-section and narrow-width implement tire. It is ideal for hay harvesting and transport applications with balers and trailers, both on- and off-the-road. It features great load capacity and a long tire life-cycle.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Baler • Hay Harvester • Trailer

|                    |               |
|--------------------|---------------|
| Version            | STANDARD      |
| Type               | TL            |
| Tyre Size          | 215/75 - 17.5 |
| LI/SS FREE ROLLING | 139 A8        |

## Dimensions International Standard

|                                   |                |
|-----------------------------------|----------------|
| <b>Ply Rating</b>                 | 16             |
| <b>Section Width (mm)</b>         | 220            |
| <b>Overall Diameter (mm)</b>      | 775            |
| <b>Static Loaded Radius (mm)</b>  | 360            |
| <b>Rolling Circumference (mm)</b> | 2310           |
| <b>Rim Rec</b>                    | 6.75           |
| <b>ECE</b>                        | E4-54R-0015341 |

## Load capacity (Kg)

|  | km/h / bar | 9.00 |
|--|------------|------|
|  | 10 FR      | 3710 |
|  | 25 FR      | 3155 |
|  | 30 FR      | 2970 |
|  | 40 FR      | 2650 |

Printed on 4/13/2024 8:50 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..