

RIB 900 - Technical Specifications



Description

RIB 900 is suitable for transport, soil tillage and hay harvesting operations with trailers, implement machinery and balers. It offers great load capacity and a long tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Hay Harvester • Implement Machinery
• Trailer

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	145 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	405
Overall Diameter (mm)	875
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2564
Rim Rec	AG 13.00
ECE	E4-106R-001551

Load capacity (Kg)

km/h / bar	3.60
10 FR	4060
25 FR	3450
30 FR	3250
40 FR	2900

Printed on 5/3/2024 8:55 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..