RIDEMAX FL 693 M - Technical Specifications

Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	169 D

Dimensions International Standard

Section Width (mm)	543
Overall Diameter (mm)	1244
Static Loaded Radius (mm)	552
Rolling Circumference (mm)	3767
SRI (mm)	600
Rim Rec	AG 16.00
Rim Alt	16.00 ; 17.00 ; AG 20.00
ECE	E11-106R-006650

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
70	1745	2165	2380	2750	3120	3435	3750	4120	4650	5280
65	1915	2380	2610	3020	3425	3770	4120	4525	5105	5800
50	2320	2880	3160	3655	4145	4565	4985	5480	6180	7020
40	2605	3235	3555	4105	4660	5130	5605	6155	6945	7890
25	3025	3760	4125	4770	5410	5960	6510	7150	8070	9165
10	3450	4285	4700	5430	6160	6790	7415	8145	9190	10440

Printed on 4/25/2024 4:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..