# RIDEMAX FL 699 - Technical Specifications

## Description

RIDEMAX FL 699 is the perfect BKT tire for road applications with trailers and tank trucks. This All Steel tire stands out for its high mileage and durability. The reinforced bead ensures better stability even at high speeds. Even if this radial tire has been designed for a 90% on-the-road usage, i.e. for transport in farming applications, the new RIDEMAX FL 699 also provides excellent performance in the fields. The tire has been designed with a particular focus on load capacity to decrease the number of transport cycles. Good news also to farmers who know the sensation when a trailer seems to compromise driving: RIDEMAX FL 699 ensures an extraordinarily comfortable ride providing safety and driving control.

## UM

US Standard

## Construction

RADIAL

## Machinery

Agriculture: Tanker • Trailer

| | |
|---|---|
| **Version** | STANDARD |
| **Type** | TL |
| **Tyre Size** | 525/65 R 20.5 |
| **LI/SS** | 173 F |

## Dimensions US Standard

| | |
|---|---|
| **Usa code** | 94066971 |
| **Ply Rating** | 20 |
| **Overall Width (inch)** | 20.4 |
| **Overall Diameter (inch)** | 47.2 |
| **Static Loaded Radius (inch)** | 21.4 |
| **Rolling Circumference (inch)** | 144.8 |
| **Rim Rec** | 16.00 |
| **ECE** | E11-54R-0018927 |

## Load capacity (lbs)

| mph / psi | 115 |
|---|---|
| **50** | 14300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 5:38 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..