

## RIDEMAX IT 697 (M+S) - Technical Specifications



### Description

RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. It is perfect for haulage and municipality applications. This winter tire for tractors ensures extraordinary grip for all operations on icy and snowy roads without the need of snow chains being mounted. Thanks to the tread grooves and the strong casing, a tractor can be driven in full stability, also at high speed levels. The tread design has been specially developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	540/65 R28 IND
LI/SS	155 D/160 A8

Dimensions US Standard

Usa code	94055401
Section Width (inch)	20.9
Overall Diameter (inch)	55.6
Static Loaded Radius (inch)	25.3
Rolling Circumference (inch)	168.3
Rim Rec	W 16 L
Rim Alt	W 18
ECE	E11-106R-004076

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	4010	4960	5810	6750	7610	8540
30	4330	5350	6270	7290	8210	9230
25	4660	5750	6750	7840	8830	9920
20	4820	5940	6970	8100	9130	10250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 11:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..