

# RIDEMAX IT 697 (M+S) - Technical Specifications



## Description

RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. It is perfect for haulage and municipality applications. This winter tire for tractors ensures extraordinary grip for all operations on icy and snowy roads without the need of snow chains being mounted. Thanks to the tread grooves and the strong casing, a tractor can be driven in full stability, also at high speed levels. The tread design has been specially developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	600/65 R 28 IND
LI/SS	165 A8/160 D

## Dimensions International Standard

Section Width (mm)	591
Overall Diameter (mm)	1491
Static Loaded Radius (mm)	684
Rolling Circumference (mm)	4509
SRI (mm)	700
Rim Rec	W 18 L
Rim Alt	DW 20 B
ECE	E11-106R-006760

## Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	2205	2700	2970	3555	4005	4500
50	2385	2920	3210	3840	4330	4860
40	2525	3090	3400	4070	4585	5150
30	2650	3240	3565	4270	4810	5400

Printed on 4/18/2024 11:28 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..