

RM 2002 - Technical Specifications



Description

RM 2002 is suitable for transport operations with trailers and light trucks, both on and off the road. It ensures long durability and top performance along the entire product life-cycle. Its "industrial" version is ideal for pick & carry cranes.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Trailer

Industrial: Mobile Crane

Version	INDUSTRIAL
Type	TT
Tyre Size	11.00 - 20

Dimensions US Standard

Usa code	94035120
Ply Rating	18
Section Width (inch)	11.9
Overall Diameter (inch)	43.3
Rim Rec	8.0
Rim Alt	7.5 ; 8.5

Load capacity (lbs)

mph / psi	120	110
62 LS	7385	-
62 LD	-	6615

Printed on 4/29/2024 3:56 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..