RT 857 - Technical Specifications

Description

RT 857 is a tire designed for soil tillage applications. Its strong casing offers excellent durability and traction. The stubble-resistant tread compound features high cut-and-chip resistance.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	460/85 R 30 (18.4 R 30)
LI/SS	145 A8/B

Dimensions International Standard

Section Width (mm)	475
Overall Diameter (mm)	1544
Static Loaded Radius (mm)	697
Rolling Circumference (mm)	4648
SRI (mm)	725
Rim Rec	W 16 L
Rim Alt	W 15 L ; W 14 L
ECE	E4-106R-001480
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1595	1860	2120	2380	2640	2900
40	1595	1860	2120	2380	2640	2900
30	1710	1990	2270	2550	2830	3105
10LT	2140	2490	2840	3190	3540	3890
10HT	1710	1990	2270	2550	2830	3105

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 7:51 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..