

SIERRA MAX PRO - Technical Specifications



Description

SIERRA MAX PRO is the perfect BKT tire for all-terrain vehicles in ATV applications, also including side-by-side racing. Its radial construction and special wider footprint area provide a smoother ride and an optimized lateral as well as forward traction. Special sturdy lugs have been studied specifically to provide excellent traction and firm grip on the terrain. These features ensure an extraordinarily comfortable ride providing safety and driving control. SIERRA MAX PRO provides excellent performance on every kind of terrain, from hardpack terrains to loose soils.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: ATV

Version	STANDARD
Type	
Tyre Size	AT 27 X 11 R 14
LI/SS	56 N

Dimensions International Standard

Section Width (mm)	285
Overall Diameter (mm)	708
Static Loaded Radius (mm)	336
Rolling Circumference (mm)	2145
Rim Rec	9.00
Star Rating	***
ECE	E11-75R-005098

Load capacity (Kg)

km/h / bar	1.2
140	224

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 1:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..