

SM 54 IND-4S - Technical Specifications

Description

SM 54 IND-4S has been specially designed for empty container handlers and reach stackers in intermodal/logistics applications. It features high stability in lift mode as well as a deep and smooth tread design, providing excellent cut resistance to ensure an extended tire life-cycle. *The picture in the gallery below refers to size 18.00-25 only.



UM

US Standard

Construction

 BIAS

Machinery

Industrial: Reach Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 - 25

Dimensions US Standard

Usa code	94015627
Ply Rating	32
Overall Width (inch)	16.9
Overall Diameter (inch)	57.9
Static Loaded Radius (inch)	26.6
Rolling Circumference (inch)	171.4
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	L4S

Load capacity (lbs)

mph / psi	145
5	37200

Printed on 4/23/2024 12:33 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..