

SR 713 - Technical Specifications



Description

SR 713 is an All Steel radial tire with VF technology for farming implements. The tire features a strong multi-ply steel-belted casing and a multi-rib tread pattern ensuring low rolling resistance and a uniform tread wear. Thanks to its large footprint, this VF tire provides reduced soil compaction. SR 713 excels in both performance and reliability offering excellent speed levels even on the road.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Implement Machinery

| | |
|-----------|------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | VF 295/75 R 22.5 |
| LI/SS | 151 D |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94057832 |
| Overall Width (inch) | 11 |
| Overall Diameter (inch) | 40.2 |
| Static Loaded Radius (inch) | 17.7 |
| Rolling Circumference (inch) | 119.8 |
| Rim Rec | 9.00 |
| Rim Alt | 8.25 |
| ECE | E11-106R-005500 |
| TRA Code | I1 |

Load capacity (lbs)

| mph/psi | 35 | 38 | 41 | 44 | 46 | 49 | 52 | 55 | 58 | 61 | 64 |
|---------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 0 | 10765 | 11360 | 12330 | 13065 | 13430 | 13800 | 14720 | 15180 | 15985 | 17020 | 17480 |
| 5 | 8425 | 8890 | 9650 | 10225 | 10510 | 10800 | 11520 | 11880 | 12510 | 13320 | 13680 |
| 10 | 8095 | 8545 | 9275 | 9825 | 10105 | 10380 | 11070 | 11420 | 12025 | 12800 | 13150 |
| 15 | 7395 | 7805 | 8470 | 8975 | 9225 | 9480 | 10110 | 10430 | 10980 | 11690 | 12010 |
| 20 | 7065 | 7460 | 8095 | 8575 | 8820 | 9060 | 9665 | 9965 | 10495 | 11175 | 11475 |
| 25 | 6365 | 6720 | 7290 | 7725 | 7940 | 8160 | 8705 | 8975 | 9450 | 10065 | 10335 |
| 30 | 5665 | 5975 | 6485 | 6875 | 7065 | 7260 | 7745 | 7985 | 8410 | 8955 | 9195 |
| 35 | 5010 | 5285 | 5735 | 6080 | 6250 | 6420 | 6850 | 7060 | 7435 | 7920 | 8130 |
| 40 | 4680 | 4940 | 5360 | 5680 | 5840 | 6000 | 6400 | 6600 | 6950 | 7400 | 7600 |
| 43 | 4260 | 4495 | 4880 | 5170 | 5315 | 5460 | 5825 | 6005 | 6325 | 6735 | 6915 |

Printed on 5/5/2024 6:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..