



## SUPER SAND - Data Sheet

### Description

SUPER SAND is particularly suitable for trailers operating on sandy surfaces during hot weather conditions. It features high flotation capability and is ideal for all operations requiring a high level of handling.



### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Trailer

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type
9.00 - 15	STANDARD	94014286	6	7.00		10.8	33.6	TT
9.00 - 16	STANDARD	94014279	8	6.50 H	6.00 G	10	34.8	TT
14.00 - 20	STANDARD	94025558	12	10.00 V	10.00 W	15.2	48.2	TT
14.00 - 20	STANDARD	94025763	16	10.00 V	10.00 W	15.2	48.2	TT
14.00 - 20	STANDARD	94028504	18	10.00 V	10.00 W	15.2	48.2	TT
16.00 - 20	STANDARD	94048359	16	10.00 W		16.3	51.4	TT

Printed on 4/27/2024 4:04 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..