

TF 9090 - Technical Specifications



Description

TF 9090 is a tire designed for small tractors in soil tillage operations. The special tread design provides excellent steering performance on loose soil.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Small Tractor
Industrial: Trailer

| | |
|-----------|------------|
| Version | SPECIAL |
| Type | TT |
| Tyre Size | 10.00 - 16 |
| LI/SS | 110 A8 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94038831 |
| Ply Rating | 8 |
| Section Width (inch) | 10.8 |
| Overall Diameter (inch) | 35.4 |
| Static Loaded Radius (inch) | 16.1 |
| Rolling Circumference (inch) | 106.9 |
| Rim Rec | W 8 |
| Rim Alt | W 8 L |
| TRA Code | F2 |

Load capacity (lbs)

| mph / psi | 44 |
|-----------|------|
| 25 | 2340 |

Printed on 12/11/2023 3:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..