

# **TF 9393 - Technical Specifications**



### **Description**

TF 9393 is an agricultural front tire specifically designed for small tractors in soils tillage applications and it is particularly suitable on loose soils. Its tread shows a wide center part and shoulder ribs. The special tread design provides excellent steering performance on all surfaces.

#### **UM**

International Standard

#### Construction



### Machinery

Agriculture: Small Tractor

| Version   | STANDARD  |
|-----------|-----------|
| Туре      | π         |
| Tyre Size | 7.50 - 16 |
| LI/SS     | 103 A6    |

### **Dimensions International Standard**

| Ply Rating            | 8               |
|-----------------------|-----------------|
| Section Width (mm)    | 210             |
| Overall Diameter (mm) | 810             |
| Rim Rec               | 5.50 F          |
| Rim Alt               | 5.00 F ; 6.00 F |
| TRA Code              | F2              |

## Load capacity (Kg)

| km/h / bar | 3.70 |
|------------|------|
| 30         | 875  |

#### Printed on 4/28/2024 6:43 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..